

Share the moment...



MP4205

PDP	Type	42" Viewable Plasma display	
	Aspect Ratio	16:9	
	Screen Size (h x v)	921.2 mm x 519.4 mm (36.27" x 20.45")	
	Resolution	852 x 480	
	Display Colors	16.7 million	
	Peak Brightness	630 cd/m ²	
	Contrast Ratio	800:1	
	Color Temperature	9000°K	
	Viewing Angle	160°	
	Cell Type	RGB Stripe (BM)	
Video Signal	PC/DTV Signal	Up to 1024 x 768 x 85 hz	
	Video System	NTSC	
	Video Signal	480i, 480p, 720p, 1080i	
	Twin Picture (PIP)	PIP	
User Control	Power Key	Power (Main/ST-BY)	
	Function Key	Input Select, Vol, +/-	
	OSD Language	English	
I/O Ports	PC Input	Video	15 pin D-sub
		Audio	Right/Left
	Composite Input	Video	2 RCA inputs
		Audio	2 RCA inputs
	S-Video Input	Video	Mini-Din 4 pin
		Audio	Right/Left
	Component Input	Video (Y, Pb, Pr)	3 component input
		Audio	Right/Left
	RF TV Tuner	Signal	NTSC
		Function	Violence protection (V-Chip), auto channel searching, auto tuning, etc
	Sound Output	Speaker (L/R)	Clinch Connector (10 w per channel)
	RS-232C		9 pin D-sub
	Remote Control		Infrared remote control
AC Input		110-240 v, 50 hz-60 hz	
Other	Power Consumption	350 watts	
	Mounting	Desk top stand, wall mount (sold separately)	
	Weight	42.64 kg (94 lbs)	
	Dimensions (w x h x d)	1056 mm x 628.6 mm x 82.55 mm (41.57" x 24.75" x 3.25") with out base	
	Accessories	15 pin VGA cable, 15 pin VGA to component cable, 110 VAC power cord, remote control, 2 x AA battery, user's manual	
	Safety Regulations	UL, CB, VCCI, FCC	

Copyright © CORNEA Systems, Inc. 2002. All rights reserved.

Windows is a registered trademark of Microsoft Corporation.
The provided information is subject to change without notice.