

Products

Overview

PD5020D

HIGH DEFINITION PLASMA MONITOR

FEATURES

- 50" Diagonal 16:9 Aspect Ratio, 1365 x 768 Resolution
- Contrast Ratio 1000:1
- Peak Brightness: 600cd/m2
- Digital DVI-I 29-Pin 1
- Video
- Composite RCA 1
- Composite BNC 1
- S-Video DIN 4-Pin 1
- DVD/HD/DTV
- Component RCA (Y,Pb(Cb),Pr(Cr)) 1
- Component BNC (Y,Pb(Cb),Pr(Cr)) 1
- Audio
- Stereo RCA 1
- External Control
- RS-232C D-Sub 9-Pin 1
- Input Signals
- RGB: VGA, SVGA, XGA, SXGA, Wide XGA
- NTSC: 3.58, 4.43
- PAL: Std, M, N, 60
- SECAM
- HD/DVD/DTV 480P(60Hz)/480I(60Hz)
- 525P(60Hz)/525I(60Hz)
- 576P(50Hz)/576I(50Hz)
- 625P(50Hz)/625I(50Hz)
- 720P(60Hz)
- 1035I(60Hz)
- 1080I(50/60Hz)

INPUTS/OUTPUTS

- RGB
- Analog BNC (R,G,B,H/C,V) 1
- Analog Mini D-sub 15-Pin 1
- Digital DVI-I 29-Pin 1
- Video
- Composite RCA 1
- Composite BNC 1
- S-Video DIN 4-Pin 1
- DVD/HD/DTV
- Component RCA (Y,Pb(Cb),Pr(Cr)) 1
- Component BNC (Y,Pb(Cb),Pr(Cr)) 1
- Audio
- Stereo RCA 1
- External Control
- RS-232C D-Sub 9-Pin 1
- Input Signals
- RGB: VGA, SVGA, XGA, SXGA, Wide XGA
- NTSC: 3.58, 4.43
- PAL: Std, M, N, 60
- SECAM
- HD/DVD/DTV 480P(60Hz)/480I(60Hz)
- 525P(60Hz)/525I(60Hz)
- 576P(50Hz)/576I(50Hz)
- 625P(50Hz)/625I(50Hz)
- 720P(60Hz)

- 1035I(60Hz)
- 1080I(50/60Hz)

-

SPECIFICATIONS

- Peak Brightness (cd/m2) 320
- Contrast Ratio (Dark Environment) 1200:1
- AccuCrimson filtering

-

GENERAL

- Sound Output 7W +7W at 6 Ohm
- Signals
- Synchronization Range Horizontal (kHz) 15.5-93.8
- (Automatic : Step Scan) Vertical (Hz) 50.0-120
- 3D Motion Adaptive Scan with Converter with 2-3 Pull Down x
- Digital Zoom x
- Auto Adjust x
- Off Timer x
- Self Diagnosis x
- Anti Image Burn x
- Color Temperature Select x
- Control Lock x
- Power Management x
- Plug and Play (DDC1, DDC2b,RGB3: DDC2b only) x
- AccuColor Control System x
- Fan x
- Multi Screen Operation x
- Wireless Remote Control x
- Regulations
- Safety & EMI/EMC
- Safety UL60950/CSA C22.2, No. 60950
- EMI/EMC FCC Class A
- General
- Dimensions Inches (W x H x D) 48 13/16" (1240mm) x 30 1/4" (766mm) x 4 1/4"
- Weight 98 lbs.
- Power Requirements 100-240 V 50/60 Hz
- Power Consumption 480 W