



- [TOP PRODUCTS](#)
- [NEWS](#)
- [ABOUT US](#)
- [SAMPO GLOBAL](#)
- [DEALER ONLY](#)

QuickLink ▼

**Products**

- [Plasma Display](#)
- [LCD](#)
- [DVD Players](#)
- [MultiMedia Monitors](#)

**Support**

**Where to Buy**

**Online Store**

## Plasma Display

### 50" High Resolution Plasma Display PME-50X6



Diagonal Screen Size	50"
Screen Aspect Ratio	16:9 Widescreen
Native Pixel Resolution	1366 x 768
Pixel Pitch	0.81mm
Brightness (Panel)	500 cd/m2
Output Color	256 RGB Levels, 16.7 million colors
Viewing Angle	160 degrees
Horizontal Frequency Range	15 kHz - 91 kHz
Vertical Frequency Range	50Hz - 85Hz
PC Signal Compatibility	VGA 640x480 @ 50, 60, 72, 75, 85 Hz SVGA 800x600 @ 56, 60, 72, 75, 85 Hz XGA 1024x768 @ 60, 70, 75, 85 Hz SXGA 1280x1024 @ 60, 75*, 85* Hz Wide VGA 852x480 @ 60 Hz; 848 x 480 @ 60Hz; DOS 720x400 @ 70 Hz VGA 640x350 @ 70 Hz * Not available via DVI
Macintosh Compatibility	640x480 @ 67 Hz 832x624 @ 75 Hz 1152x870 @ 75 Hz

[PME-50X6](#)

[PME-50X6](#)

[PME-50X6 Specificati](#)

[Plasma Wa](#)

[Extended V](#)

Adobe Acro is required files. Click o Acrobat ima download it



**PRODUCTS**



[50" High Res Display  
PME-50X6](#)

With new fea DVI-D Input PME-50X6 is addition to yr theater!



[17" Ultra-Thin  
LME-17S3](#)

Versatile. Sty The space-s 17S3 deliver pictures.



[DVD/Karaoke  
Decoder  
DVE-662](#)

Have a kara the new DVE DVD Player! with your fav

Video System Compatibility	NTSC, PAL
HDTV Video Compatibility	480i, 480p, 1080i, 720p SDTV/EDTV/HDTV
Input Terminals	AV 1 Composite RCA x1 AV 2 S-Video 4-pin DIN x1 Component 1 1 Set auto-sync RCA x3 (Y,Pb,Pr/Y,Cb,Cr) Component 2 1 Set auto-sync RCA x3 (Y,Pb,Pr/Y,Cb,Cr) RGB (Analog) 15-pin D-Sub x1 DVI 24-pin DVI x1 Audio 6 Sets RCA stereo inputs
Output Terminals	Audio 1 Set RCA stereo output RGB 15-pin D-Sub x1 Subwoofer 1 RCA output
External Controls	RS232 9-pin D-Sub x1
Power Supply	100V ~ 240V / 50 ~ 60 Hz
Power Consumption	470 Watts ±10%
Dimensions (WxHxD)	With Stand 1256 x 810 x 321 mm (49.45 x 31.9 x 12.64 in) Without Stand 1256 x 762 x 107.5 mm (49.45 x 30 x 4.23 in)
Environmental Considerations	Operating Temperature 32~105 degrees F Operating Humidity 20~80% Operating Pressure .8-1.1 atmospheric pressure
Warranty	1-Year parts & labor
Regulatory	FCC Class B
Included Accessories	Table stand, Remote control, Batteries, User manual, Power cable, VGA cable
Optional Accessories	Wall mount, TV tuner module

videos on thi  
player.



[32" Pure Fla  
SME-32FDL](#)

From school conferencing  
the SME-32f  
superior perf  
your present

[Click here to go back.](#)